



## Bronze Swing Check Valves 150 lb

**SIZES: 1/2" to 12"**

**PRESSURE / TEMPERATURE RATINGS**  
150 PSI WSP 550°F / 225 PSI WOG 150°F

### DESIGN DESCRIPTION

- Flanged Ends
- Threaded Bonnet (1/2" to 2") or Bolted Bonnet (2-1/2" to 12")
- Bronze Body Material, ASTM B62
- Aluminum Bronze Trim or Monel Trim Material


Face to face conforms to ASME B16.10.

### DIMENSIONS (Inches): Threaded Bonnet

SIZE	1/2	3/4	1	1-1/4	1-1/2	2
FF	4.25	4.45	5.00	5.51	6.50	7.99
D	3.54	3.94	4.33	4.53	4.92	5.91
wt	3	4	5	7	9	15

### DIMENSIONS (Inches): Bolted Bonnet

SIZE	2-1/2	3	4	5	6	8	10	12
FF	8.50	9.49	11.50	12.99	14.02	19.49	24.49	27.48
D	7.09	7.48	9.06	10.04	11.02	13.58	15.95	19.10
wt	31	39	67	102	130	280	400	600



**ALUM. BRONZE TRIM**  
ITEM ID: 052503



**MONEL TRIM**  
ITEM ID: 052504